

SKF 729659 C/110V

Electric Hot Plate



The SKF 729659 C is a heating device especially designed for pre-heating batches of small bearings prior to mounting. The temperature of the plate can be adjusted to provide temperatures between 50 and 200 °C (120 and 390 °F). The flat heating surface ensures even bearing heating and the cover helps to retain heat and keep contaminants out.

- Thermostat controlled hot plate
- Designed for heating batches of small bearings
- With cover to retain heat and protect bearings against contaminants
- Flat heating surface for even bearing heating

Dimensions

Dimensions (W x L x H)	15.4 x 7.5 x 5.5 in
------------------------	---------------------

Properties

Recommended applications	Conveyors;OEM;Electrial motors
Type	Hotplate
Series	729659 C
Heating method	Heating plate
Suitable for mounting	Yes
Suitable for dismounting	No
Solid workpiece weight (max, mounting)	8.82 lb
Bearing weight (max)	8.82 lb
Workpiece bore diameter (mounting)	0.1969 – 3.937 in
Workpiece outer diameter	0.4331 – 7.0079 in
Power consumption (max)	1000 W
Workpiece width (max)	1.7717 in
Voltage	100-120 V
Voltage frequency	50 / 60 Hz
Current (max)	10 A
Temperature measurement	Integrated
Demagnetisation after heating	No, not needed
Heating temperature (max)	392 °F

Forced air cooling	No
Thermometer mode	No
Time mode	No
Remote control panel (wired)	No
Heating temperature control	122 – 392 °F
Heating temperature steps	41 °F
Housing material	Steel
Material	Steel
Coating	Steel
Colour	Blue;Dark grey
Content	Hotplate with lid, spare Celcius knob

Logistics

Country of Manufacturing (COM code)	16 - Netherlands
Product net weight	13.2 lb
eClass code	23-05-19-01
UNSPSC code	40101831

Compatible products

Type	Designation	Description	Qty
Spare part	729659 C-1	Heaters	1