SKF HN 1

Hook spanner

The SKF Hook spanner, size 1, is designed for easy tightening and loosening of lock nuts. They are used to secure and adjust bearings on tapered journals, adapter sleeves and withdrawal sleeves. They fit on a variety of lock nuts with outer diameter(s) 20 - 22 mm. To be more specific for locknuts: KM 1, KMK 1, N 01 and (DIN 1804).

- Optimised design allow use in narrow spaces while maintaining maximum force
- Sturdy plastic handle that is oil, dirt and grease resistant to provide a better grip
- Drilled hole for easy hanging storage
- Laser-engraved designation for easy identification
- They fit on a variety of locknuts with outer diameter(s) 20 - 22mm

Dimensions

Outer diameter lock nut (range) (d■)	0.7874 – 0.8661 in
Nose width (N■)	0.1181 in
Nose height (N■)	0.0787 in
Thickness (n)	0.1181 in
Length (L)	4.2913 in
Working length (l)	3.937 in
Height	0.4724 in

Properties

Recommended applications	For applications that require tightening/loosening a wide variety of lock nuts on shafts, adapter sleeves, and withdrawal sleeves.
Series	Hook spanner, standard, HN
Type	Model B
Allows bearing mounting	Yes, angle method or with clearance reduction measurement
Size according DIN 1810	0.79 to 0.87 in
Fits on lock nuts inside SKF split pillow block housings (SNL)	No
Locknut size	1 – 1
Suitable SKF Locknut	KM 1, KMK 1, N 01
Material	Medium carbon steel, hardened and tempered
Material handle	Durable soft plastic

Coating	Black phosphated
Colour	Black, with red handle
Part of a kit	No

Logistics

Country of Manufacturing (COM code)	35 - Slovenia
Product net weight	0.044 lb
eClass code	23-05-19-01
UNSPSC code	27111712

Compatible products

Type	Designation	Description	Qty
Recommended product	**KM 1**	Lock nut with metric thread, for locking by lock washer	1
Recommended product	**KMK 1**	Lock nut with metric thread, with integral locking device	1
Recommended product	**N 01**	Lock nut with inch thread, for locking by lock washer or locking plate	1