

SKF HN 18-20

Hook spanner



The SKF Hook spanner, size 18 - 20, is designed for easy tightening and loosening of lock nuts. They are used to secure and adjust bearings on tapered journals, adapter sleeves and withdrawal sleeves. They fit on a variety of lock nuts with outer diameter(s) 120 - 130 mm. To be more specific for locknuts: KM 18, KM 19, KM 20, KMK 18, KMK 19, KMK 20, KMFE 18, KMFE 19, KMFE 20, KMT 17, KMT 18, KMT 19, AN 18, AN 19, AN 20 and M85x2, M90x2 (DIN 1804).

- Optimised design allow use in narrow spaces while maintaining maximum force
- Sturdy plastic handle that is oil, dirt and grease resistant to provide a better grip
- Drilled hole for easy hanging storage
- Laser-engraved designation for easy identification
- They fit on a variety of locknuts with outer diameter(s) 120 - 130mm

Dimensions

Outer diameter lock nut (range) (d $\blacksquare$)	4.7244 – 5.1181 in
Nose width (N $\blacksquare$)	0.3937 in
Nose height (N $\blacksquare$)	0.1575 in
Thickness (n)	0.3937 in
Length (L)	13.1496 in
Working length (l)	11.0236 in
Height	3.189 in

Properties

Recommended applications	For applications that require tightening/loosening a wide variety of lock nuts on shafts, adapter sleeves, and withdrawal sleeves.
Series	Hook spanner, standard, HN
Type	Model B
Allows bearing mounting	No
Size according DIN 1810	4.72 to 5.12 in
Fits on lock nuts inside SKF split pillow block housings (SNL)	No
Locknut size	18 – 20
Suitable SKF Locknut	KM 18, KM 19, KM 20, KMFE 18, KMFE 19, KMFE 20, KMK 18, KMK 19, KMK 20, KMT 17, KMT 18, KMT 19, AN 18, AN 19, AN 20
Material	Medium carbon steel, hardened and tempered

Material handle	Durable soft plastic
Coating	Black phosphated
Colour	Black, with red handle
Part of a kit	No

Logistics

Country of Manufacturing (COM code)	35 - Slovenia
Product net weight	1.72 lb
eClass code	23-05-19-01
UNSPSC code	27111712

Compatible products

Type	Designation	Description	Qty
Recommended product	AN 18	Lock nut with inch thread, for locking by lock washer	1
Recommended product	AN 19	Lock nut with inch thread, for locking by lock washer	1
Recommended product	AN 20	Lock nut with inch thread, for locking by lock washer	1
Recommended product	KM 18	Lock nut with metric thread, for locking by lock washer	1
Recommended product	KM 19	Lock nut with metric thread, for locking by lock washer	1
Recommended product	KM 20	Lock nut with metric thread, for locking by lock washer	1
Recommended product	KMFE 18	Lock nut with metric thread, with locking screw	1
Recommended product	KMFE 19	Lock nut with metric thread, with locking screw	1
Recommended product	KMFE 20	Lock nut with metric thread, with locking screw	1
Recommended product	KMK 18	Lock nut with metric thread, with integral locking device	1
Recommended product	KMK 19	Lock nut with metric thread, with integral locking device	1
Recommended product	KMK 20	Lock nut with metric thread, with integral locking device	1
Recommended product	KMT 17	Precision lock nut with locking pins	1
Recommended product	KMT 18	Precision lock nut with locking pins	1
Recommended product	KMT 19	Precision lock nut with locking pins	1