SKF TMFS 17

Axial lock nut socket

The TMFS axial lock nut sockets are used to mount bearings on tapered journals or adapter sleeves and for dismounting bearings on withdrawal sleeves. Available in 21 different sizes, they are suitable for various locknuts sizes 0 to 20.

- Good alternative to hook spanners, making the use of power tools or torque wrenches possible
- Allow the use of torque wrenches
- The sockets are provided with a zinc flake coating to assure corrosion protection.

Dimensions

Locknut size	17 – 17
Outer diameter lock nut (range) (d■)	4.3307 – 4.3307 in
Drive connection (C)	1"
Height	4.3307 in
Effective height (h)	3.1496 in
Outer diameter	4.7638 in

Properties

Recommended applications	For a controlled use with torque wrenches or power tools for safe tightening or loosening of lock nuts on shafts, adapter sleeves, and withdrawal sleeves or in blind housings. Also particullarly suitable for applications where space limitations prevent the use of hookspanners.
Series	Axial lock nut socket, TMFS
Type	Model A
Allows bearing mounting	No
Fits on lock nuts inside SKF split pillow block housings (SNL)	No
Suitable SKF Locknut	KM 17, KMFE 17, KMK 17
Material	Alloy engineering steel, hardened and tempered
Coating	Black oxide
Colour	Black metallic

Logistics

Country of Manufacturing (COM code)	45 - India
Product net weight	5.71 lb
eClass code	23-05-19-01
UNSPSC code	27111712