

SKF TMMR 350XL

Reversible jaw puller, long arms



The multi-purpose SKF Reversible Jaw Puller TMMR 350XL is designed for internal and external pulling jobs of bearings and other components such as gears and pulleys. The puller features an extra long arm set which can be extended further with optional arm extensions. The two arms of the puller can be mounted with the claws facing inside or facing outside, making it a versatile and essential tool for mechanical workshops.

- Easy adjustment of the width of grip with self-locking arms
- Essential and versatile tools for every workshop for internal and external pulling applications
- Enhanced corrosion resistance and easy cleaning with zinc passivated arms and beam
- No permanent deformation of puller arms when used up to maximum withdrawal force
- Optional accessories further increase the versatility of the puller

Logistics

Country of Manufacturing (COM code)	35 - Slovenia
Product net weight	11.1 lb
eClass code	23-05-19-01
UNSPSC code	27111712

Properties

Recommended applications	For the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Yes
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Yes
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Yes
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	No
Suitable for workpiece dismounting from a Housing	Yes, with spindle support (not included)
Suitable for bearing type(s)	All
Dismounting force generation	Spindle
Special features	Reversible arms;Selflocking arms; Extendable arms;Nosepiece with spring loaded tip
Number of arms	2

Width of grip external	1.7323 – 13.2283 in
Width of grip internal	4.8425 – 15.1181 in
Effective arm length	8.7008 in
Total Arm length	12.9 in
Claw height	0.3346 in
Claw length	0.6299 in
Claw width	0.9843 in
Spindle torque (max)	118 lbf·ft
Spindle head, hexagon size	24
Puller or Adapter hexagon size	1.2598 in
Spindle nose piece	Yes, ■1.9 in
Material	Alloy engineering steels, hardened and tempered
Coating	Zinc coated
Content	1x Puller TMMR 350XL;1x Nosepiece;1x Tube of spindle grease LGEV2/0.035;1x Printed instructions for use

Dimensions

Total spindle length	14.5 in;15.7 in with nosepiece
----------------------	--------------------------------

Compatible products

Type	Designation	Description	Qty
Refill	LGEV 2/0.035	Extremely high viscosity bearing grease with solid lubricants	1
Spare part	TMMR 350F-2	Spare beam for Reversible jaw puller	1
Spare part	TMMR 350F-3	Spare spindle for Reversible jaw puller	1
Spare part	TMMR 25/35XL-1	Accessory long arms set, with extra nose piece for Reversible jaw pullers	1
Accessory	TMMR 350F-1	Spare arm for Reversible jaw puller	2
Accessory	TMMR 16/35XL-4	Accessory arm extender set including bolts for long arms of Reversible jaw pullers	1
Accessory	TMMR 16/35XL-5	Spare nose piece spring-loaded for long arms of Reversible jaw pullers	1
Recommended product	TMMR 40F	Reversible jaw puller	1
Recommended product	TMMR 60F	Reversible jaw puller	1
Recommended product	TMMR 80F	Reversible jaw puller	1
Recommended product	TMMR 120F	Reversible jaw puller	1
Recommended product	TMMR 160F	Reversible jaw puller	1
Recommended product	TMMR 200F	Reversible jaw puller	1

Type	Designation	Description	Qty
Recommended product	TMMR 250F	Reversible jaw puller	1
Recommended product	TMMR 350F	Reversible jaw puller	1
Recommended product	TMMR 160XL	Reversible jaw puller, long arms	1
Recommended product	TMMR 200XL	Reversible jaw puller, long arms	1
Recommended product	TMMR 250XL	Reversible jaw puller, long arms	1
Recommended product	TMMR 4F/SET	Reversible jaw puller set	1